

SNK-2216 (Aliphatic Polyurethane Acrylate)

Basic Information

Place of Origin: Wuhan, Hubei, China
Brand Name: Meilun Materials
Model Number: SNK-2216
Minimum Order Quantity: 20kg

• Packaging Details: 20kg/barrel, 200kg/barrel

Payment Terms: L/C, T/TSupply Ability: 50T/month



Product Specification

• Highlight: Vacuum Plating Resin, SNK-2216Plating Resin,

water resistance Aliphatic Polyurethane

Acrylate

Product Description

UV Metal Adhesion Resin(Aliphatic polyurethane acrylate) SNK-2216

Product Description:

Main applications: This is a high-durability, high-curing, and high-hardness resin.

Processes include screen printing, roller coating, spraying, adhesive applications, etc. It can be mixed with conventional UV monomers and resins.

Typical performance characteristics:

- 1:Excellent mar resistance, high hardness, good water resistance, fast curing, and suitable for LED curing. 2:Number of functional groups: 6, curing energy: 300-500 mJ/cm², suitable for curing with UV and UV-LED.
- 3:Molecular weight (Mw): 1500-3000, soluble in ketones, esters, and aromatic solvents.

Technical Parameters:

serial number	Technical parameter items	unit	Technical parameters
1	viscosity	mpa.s/60°C	3000-6000
2	Solid content	%	≥98
3	Exterior		Slightly yellow viscous
4	color number	Gardner,25°C	<1
5	AV	mgKOH/g	≤3
6	NCO	mgKOH/g	≤3
7	Polymerization inhibitor	ppm	< 400

Storage and validity period:

- 1: This product should be stored in a cool, well-ventilated room, and strictly protected from light exposure for stable storage.
- 2: Keep the resin away from heat sources and store it in a dark place to prevent potential hazards or affecting the stability of resin storage.
- 3: When stored at room temperature, it remains stable for six months. After use, please tightly seal the container to avoid exposure to light sources and gelation.

Package

200 kilograms/iron drum 20 kilograms/iron drum 200 kilograms/plastic drum 20 kilograms/plastic drum

Wuhan Meilun New Materials Co., Ltd



+8618062439876



